

Oven

Constant-Temperature Drying Oven

Features:

- * External material: cold-rolled steel with anti-bacteria powder coating.
- * Stainless steel inner chamber, round angle structure, adjustable shelves.
- * PID control with LED display, soft touch operational key, timing function and over-temperature protection.
- * Door with double-layer tempered glass observation window, adjustable air-tight buckle lock, and silicon rubber seal, which provide good seal ability and efficiently prevent heat loss.



Technical Parameters:

| Model | DRONC43 | DRONC72 | DRONC137 | DRONC270 |
|-------------------------|--------------------------|-------------|-------------|---------------|
| Capacity | 43L | 72L | 137L | 270L |
| Temp. Range | 50~200°C | | | |
| Temp. Fluctuation | ±1°C | | | |
| Ambient Temp. | 5~40°C | | | |
| Timing Range | 1~9999min | | | |
| Shelves No. | 2 pcs | | 3 pcs | |
| Consumption | 850W | 1000W | 2000W | 3000W |
| Power Supply | AC110V/220V±10%, 50/60Hz | | | |
| Internal Size(W*D*H) mm | 350*350*350 | 400*400*450 | 500*500*550 | 600*600*750 |
| External Size(W*D*H) mm | 630*540*550 | 720*570*750 | 820*670*850 | 920*770*1050 |
| Package Size(W*D*H) mm | 780*750*700 | 870*700*800 | 960*780*950 | 1060*880*1150 |
| Gross Weight(kg) | 60 | 70 | 105 | 145 |